

IP67

2 YEAR WARRANTY



STANDARD DRIVER

CE RoHS

Specifications

MODEL		LPH-18-12	LPV-20-12	LPV-35-12	LPV-60-12	LPV-100-12
OUTPUT	DC VOLTAGE	12V				
	RATED CURRENT	1.5A	1.67A	3A	4A	8.5A
	CURRENT RANGE	0 ~ 1.5A	0 ~ 1.67A	0 ~ 3A	0 ~ 4A	0 ~ 8.5A
	RATED POWER	18W	20W	36W	60W	102W
INPUT	VOLTAGE RANGE	180 ~ 264VAC	90 ~ 264VAC		90 ~ 264VAC 127 ~ 370VDC	
	FREQUENCY RANGE	47 ~ 63Hz				
	AC CURRENT	0.3A/230VAC	0.55A/115VAC 0.35A/230VAC	1.1A/115VAC / 0.7A/230VAC	1.2A/115VAC 1A/230VAC	2.2A/115VAC 1.2A/230VAC
	INRUSH CURRENT (MAX)	Cold start 50A/230VAC	Cold start 35A/115VAC 70A/230VAC	Cold Start 30A/115VAC / 60A/230VAC		Cold start 30A/115AVC 75A/230VAC
WORKING TEMPERATURE		-25 ~ 70°C	-30 ~ 70°C	-30 ~ 75°C	-30 ~ 70°C	-25 ~ 70°C
DIMENSIONS		140 x 30 x 20mm	118 x 35 x 26mm	148 x 40 x 30mm	162.5 x 42.5 x 32mm	190 x 52 x 37mm

MODEL		LPH-18-24	LPV-20-24	LPV-35-24	LPV-60-24	LPV-100-24
OUTPUT	DC VOLTAGE	24V				
	RATED CURRENT	0.75A	0.74A	1.5A	2.5A	4.2A
	CURRENT RANGE	0 ~ 0.75A	0 ~ 0.84A	0 ~ 1.5A	0 ~ 2.5A	0 ~ 4.2A
	RATED POWER	18W	20.2W	36W	60W	100.8W
INPUT	VOLTAGE RANGE	180 ~ 264VAC	90 ~ 264VAC		90 ~ 264VAC 127 ~ 370VDC	
	FREQUENCY RANGE	47 ~ 63Hz				
	AC CURRENT	0.3A/230VAC	0.55A/115VAC 0.35A/230VAC	1.1A/115VAC / 0.7A/230VAC	1.2A/115VAC 1A/230VAC	2.2A/115VAC 1.2A/230VAC
	INRUSH CURRENT (MAX)	Cold start 50A/230VAC	Cold start 35A/115VAC 70A/230VAC	Cold Start 30A/115VAC / 60A/230VAC	Cold start 60A (twidh=525µs mea- sured at 50% Ipeak) at 230VAC	Cold start 30A/115AVC 75A/230VAC
WORKING TEMPERATURE		-25 ~ 70°C	-30 ~ 70°C	-30 ~ 75°C	-30 ~ 70°C	-25 ~ 70°C