



STANDARD DRIVER



Specifications

MODEL		RS-25-12	RS-50-12	RS-100-12	RS-150-12	SP-200-12	SP-320-12
OUTPUT	DC VOLTAGE	12V					
	RATED CURRENT	2.1A	4.2A	8.5A	12.5A	16.7A	25A
	CURRENT RANGE	0 ~ 2.1A	0 ~ 4.2A	0 ~ 8.5A	0 ~ 12.5A	0 ~ 16.7A	0 ~ 25A
	RATED POWER	25.2W	50.4W	102W	150W	200.4W	300W
INPUT	VOLTAGE RANGE	88 ~ 264VAC 125 ~ 373DC			88 ~ 132VAC / 176 ~ 264VAC 248 ~ 373VDC	85 ~ 264VAC / 120 ~ 370VDC	88 ~ 264VAC / 124 ~ 370VDC
	FREQUENCY RANGE	47 ~ 63Hz					
	AC CURRENT	0.7A/115VAC 0.4A/230VAC	1.3A/115VAC 0.8A/230VAC	2.5A/115VAC 1.5A/230VAC	3A/115VAC 2A/230VAC	3.5A/115VAC 1.7A/230VAC	5A/115VAC 2.5A/230VAC
	INRUSH CURRENT (MAX)	Cold start 30A/230VAC	Cold start 33A/230VAC	Cold Start 40A/230VAC	Cold start 40A/230vac	Cold start 40A/230VAC	Cold start 40A/230VAC
WORKING TEMPERATURE		-25 ~ 70°C					
DIMENSIONS		79 x 51 x 28mm	99 x 97 x 36mm	159 x 97 x 38mm	199 x 98 x 38mm	199 x 99 x 50mm	215 x 115 x 50mm

MODEL		RS-25-24	RS-50-24	RS-100-24	RS-150-24	SP-200-24	SP-320-24
OUTPUT	DC VOLTAGE	24V					
	RATED CURRENT	1.1A	2.2A	4.5A	6.5A	8.4A	13A
	CURRENT RANGE	0 ~ 1.1A	0 ~ 2.2A	0 ~ 4.5A	0 ~ 6.5A	0 ~ 8.4A	0 ~ 13A
	RATED POWER	26.4W	52.8W	108W	156W	201.6W	312W
INPUT	VOLTAGE RANGE	88 ~ 264VAC 125 ~ 373DC			88 ~ 132VAC / 176 ~ 264VAC 248 ~ 373VDC	85 ~ 264VAC / 120 ~ 370VDC	88 ~ 264VAC / 124 ~ 370VDC
	FREQUENCY RANGE	47 ~ 63Hz					
	AC CURRENT	0.7A/115VAC 0.4A/230VAC	1.3A/115VAC 0.8A/230VAC	2.5A/115VAC 1.5A/230VAC	3A/115VAC 2A/230VAC	3.5A/115VAC 1.7A/230VAC	5A/115VAC 2.5A/230VAC
	INRUSH CURRENT (MAX)	Cold start 30A/230VAC	Cold start 33A/230VAC	Cold Start 40A/230VAC	Cold start 40A/230vac	Cold start 40A/230VAC	Cold start 40A/230VAC
WORKING TEMPERATURE		-25 ~ 70°C					